



JMH65R190PCFD

Features

- Excellent $R_{DS(ON)}$ and Low Gate Charge
- 100% UIS Tested
- 100% $\bar{u}V_{ds}$ Tested
- Halogen-free; RoHS-compliant

Applications

- SMPS with PFC
- Flyback
- Silver ATX, adapter, TV, lighting, Telecom

Product Summary


Parameters	Value	Unit
V_{DSS}	650	V
$V_{GS(th_Typ)}$	3.4	V
$I_D(@V_{GS}=10V)$	15	A
$R_{DS(ON)_Typ}(@V_{GS}=10V)$	156	$m\Omega$



TO-220-3L Top View



Pin Assignment



Schematic Diagram

Ordering Information

Device	Marking	MSL	Form	Package	Tube(pcs)	Per Carton (pcs)
JMH65R190PCFD-U	H65R190PF	N/A	Tube	TO-220-3L	50	5000

Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit
V_{DS}	Drain-to-Source Voltage	650	V
V_{GS}	Gate-to-Source Voltage	± 30	V
I_D	Continuous Drain Current	$T_C = 25^\circ\text{C}$	15
		$T_C = 100^\circ\text{C}$	10
I_{DM}	Pulsed Drain Current ⁽¹⁾	Refer to Fig.4	A
E_{AS}	Single Pulsed Avalanche Energy ⁽²⁾	65	mJ
P_D	Power Dissipation	$T_C = 25^\circ\text{C}$	114
		$T_C = 100^\circ\text{C}$	45
T_J, T_{STG}	Junction & Storage Temperature Range	-55 to 150	$^\circ\text{C}$


Thermal Characteristics

Symbol	Parameter	Max	Unit
$R_{\theta J-A}$	Thermal Resistance, Junction to Ambient ⁽³⁾	68	$^\circ\text{C}/\text{W}$
$R_{\theta J-C}$	Thermal Resistance, Junction to Case	1.1	

Electrical Characteristics (T_J = 25°C unless otherwise specified)

Symbol	Conditions	Min.	Typ.	Max.	Unit
Off Characteristics					
V _{(BR)DSS}		650	-	-	V
I _{DSS}		-	-	10.0	μA
I _{GSS}		-	-	±100	nA
V _{GS(th)}		2.4	3.4	4.5	V
R _{DS(ON)}		-	156	190	mΩ
R _g		-	4.9	-	Ω
C _{iss}		1084	1517	2049	pF
C _{oss}		28	39	52	pF
C _{rss}		-	5.9	-	pF
Q _g		23	32	43	nC
Q _{gs}		-	10	-	nC
Q _{gd}		-	11	-	nC
t _{d(on)}		-	36	-	ns
t _r	V _{GS} = 10V, V _{DD} = 310V	-	38	-	ns
t _{d(off)}	I _D = 10A, R _{GEN} = 24Ω	-	100	-	ns
t _f	Turn-Off Fall Time	-	30	-	ns
Body Diode Characteristics					
I _S		-	-	15	A
I _{SM}		-	-	61	A
V _{SD}	Body Diode Forward Voltage	V _{GS} = 0V, I _S = 10A		1.2	V
t _{rr}	Body Diode Reverse Recovery Time	I _F = 10A, di/dt = 100A/us		177	ns
Q _{rr}	Body Diode Reverse Recovery Charge	-	851	-	nC

- Notes:
1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
 2. E_{AS} condition: Starting T_J=25°C, V_{DD}=50V, V_{GS}=10V, R_G=25ohm, L=10mH, I_{AS}=3.6A, V_{DD}=0V during time in avalanche.
 3. R_{θ(jc)} is measured with the device mounted on FR-4 substrate PC board, 2oz copper, with minimum recommended pad layout.
 4. Pulse Test: Pulse Width V X W \ & 0.5% .H



Typical Performance Characteristics

Figure 1: Power De-rating








Figure 2: Current De-rating



Typical Performance Characteristics

Figure 5: Output Characteristics



Test Circuit



Figure 1: Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveform




Figure 3: Unclamped Inductive Switching Test Circuit & Waveform



Figure 4: Diode Recovery Test Circuit & Waveform



Package Mechanical Data(TO-220-3L)

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may