

Peak gate power	P_{GM}	10	W
Peak pulse voltage ($T_j=25$; non-repetitive, off-state; FIG.7)	V_{pp}	2.5	kV

ELECTRICAL CHARACTERISTICS (unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	$V_D=12V$ $R_L=33$	- -	MAX.	50	mA
V_{GT}		- -	MAX.	1	V
V_{GD}	$V_D=V_{DRM}$ $T_j=125$ $R_L=3.3k$	- -	MIN.	0.2	V

I_L $I_G=1.2I_{GT}$

ORDERING INFORMATION

<u>J</u>	<u>ST</u>	<u>08</u>	<u>A</u>	<u>-1200</u>	<u>BW</u>
JieJie Microelectronics Co., Ltd.	Triacs	$I_{T(RMS)}:8A$			
		<u>A:TO-220A(Ins)</u>			<u>BW:IGT1-3 50mA</u>
				<u>1200:V_{DRM} /V_{RRM} 1200V</u>	

MARKING




FIG.1: Maximum power dissipation versus RMS

ORDERING INFORMATION

Order code	Voltage V _{DRM} /V _{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery	RMRRM

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents.

Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. Thi4 ()JTJ 0.004 T pat proc