



DESCRIPTION:

The JST12A-1000BW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST12A-1000BW snubberless triac is especially recommended for use on inductive loads. By using an internal ceramic pad, JST12A-1000BW provides a rated insulation voltage of 2500 VRMS, complying with UL standards (File ref: E252906). Package TO-220A is RoHS compliant.

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage ($T_j=25^\circ\text{C}$)	V_{DRM}	1000	V
Repetitive peak reverse voltage ($T_j=25^\circ\text{C}$)	V_{RRM}	1000	V
RMS on-state current ($T_c 086^\circ\text{C}$)	$I_{T(RMS)}$	12	A

Non repetitive surge peak on-state current
(full cycle , t_p)

JST12A-1000BW

ORDERING INFORMATION

J	ST	12	A	-1000	BW
JieJie Microelectronics Co., Ltd.	Triacs	$I_T(RMS):12A$	A:TO-220A(Ins)		BW:IGT1-3 050 mA
				1000:V _{DRM} /V _{RRM} 11000 V	

MARKING



	
---	--

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature



FIG.7 ÖTest circuit for inductive and resistive loads to IEC-61000-4-5 standards

ORDERING INFORMATION

Order code	Voltage $V_{\text{DRM}}/V_{\text{RRM}}$ (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		H- I- J			
JST12A-1000BW	1000	50	TO-220A(Ins)	50	Tube

Document Revision History

Date	Revision	Changes
Apr.11, 2023	A.1.0	Last updated
Oct.13, 2025	A.1.1	Revise PACKAGE MECHANICAL DATA

