

Peak pulse voltage (T _{on} ≤ 100μs; non-repetitive; 25°C; FIG.7)	V _{pp}	2.5	V
--	-----------------	-----	---

ELECTRICAL CHARACTERISTICS (unless otherwise specified)

Symbol	Test Condition	Quadrant	Value	Unit
I _{GT}	V _D = 12V, R _L = 33Ω	MAX	35	mA

ORDERING INFORMATION

FIG.1: Maximum power dissipation vs RMS current



FIG.2: RMS current vs temperature

FIG.7 Test circuit for inductance and resistance IEC

-61000-45 standards



ORDERING INFORMATION

Order code	Voltage V _{DRM} /V _{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		H I- J			
JST24C-800CW	800	35	TO-220C	50	Tube

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, JiangJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of any consideration for any information nor beyond it. Information mentioned in this document is subject to change without notice, apart from that an agreement is signed, JiangJie Microelectronics Co., Ltd. complies with the agreement.

Products and information provided in this document have no infringement of patents. JiangJie Microelectronics Co., Ltd. assumes no responsibility for any infringement of other rights of third parties which may result from the use of any products and information. This document describes and replaces all information previously applied.

 is a registered trademark of JiangJie Microelectronics Co., Ltd.

Copyright © 2025 JiangJie Microelectronics Co., Ltd. All rights reserved.